



74,2_{hp}



TRANSMISSION
16+16
SYNCH. INVERTER

40
Km



PROTECTOR

EXG
MAXIMUM
PROTECTION
GUARANTEE

5
STAGE

Frame	ACTIO™ integral oscillating frame • Steering wheels • Four different-size driving wheels • Front and rear final drives
Engine type	8900 KUBOTA - Direct injection diesel - 4 Cylinders - 16 Valves - TURBO Stage 5 - Common rail - 3769 cc Power 54.6 kW / 74.2 hp - 2400 rpm Max torque 305 Nm at 1500 rpm
Transmission	32 speed synchronised gearbox: 16 FWD + 16 REV with synchronised shuttle
Power take-off	Rear, independent and synchronized at 540/540E rpm with progressive electrohydraulic engagement
Hydraulic system	Load-sensing hydraulic system. Rear auxiliary hydraulics with 1 double-acting floating valve and 1 oil return
Rear power lift	3 point hitch Operating - Category C rear trailer hitch, height adjustable - Front tow hook - Pressure 160 bar - Capacity 2400 Kg
Brakes	Standard: hydraulic front and rear disk brakes in oil bath, rear steering brakes - Independent emergency and parking brake: band type on transmission
Weight	With roll bar (Kg): 2160 ÷ 2340 - With PROTECTOR cab (Kg): 2320 ÷ 2520 - With Star Light cab (Kg):

DIMENSIONS WITH STANDARD WHEELS: FRONT 8.25-16 REAR 280/85 R20

	A	B	C	D	F	G	H	I	L
TGF 8900	3555÷4020	1225	1465	865÷1035	2310	250	1785	2070	1330

